PG&E CASE Report Revise Default EER in ACM

PG&E Codes and Standards
Enhancement (CASE) Project
December 17, 2007
Title 24 Committee hearing





Federal Air Conditioner Efficiency

- Central Air Conditioners < 65,000 Btu/h</p>
 - Federal efficiency standard "covered" equipment
- Single phase air conditioners and heat pumps manufactured after Jan 2006 at least SEER 13
- SEER seasonal energy efficiency ratio
- Pre-empted from state regulation






EER vs SEER

- SEER (seasonal energy efficiency ratio)
 measured at 82°F and under part load
 - Not representative of peak conditions or typical conditions in eastern part of state
- EER (energy efficiency ratio) rated at 95°F ambient temp at full load output
 - Test conditions used to rate capacity of air conditioner
 - Representative of typical conditions in CA hot dry climates in central valley
 - More representative than SEER of peak demand conditions
 - Manufacturer not required to report or label EER





ACM Model of temperature dependent efficiency, EERt







CEC and ARI databases of SEER 13 central air conditioners


	CEC	CEC	CEC % Cumu	A.D.Y. //	ARI %	ARI % Cumu
EER Bin	#	% Total	lative	ARI#	Total	lative
Less than 10	0	0.0%	0.0%	148	0.4%	0.4%
10.0 to 10.5	14	1.9%	1.9%	1,141	3.4%	3.8%
10.6 to 10.9	62	8.6%	10.5%	1,997	6.0%	9.8%
11.0 to 11.3	283	39.3%	49.8%	22,516	67.1%	76.9%
11.4 to 11.6	88	12.2%	62.0%	4,178	12.5%	89.4%
11.7 to 11.9	74	10.3%	72.3%	2,587	7.7%	97.1%
12.0 to 12.9	200	27.7%	100.0%	964	2.9%	99.99%
13 and more	0	0.0%	100.0%	3	0.01%	100.0%
Total	721	100%		33,534	100%	



Only 10% of models have EERs less than 11.



Distribution of EERs for SEER 13 air conditioners sold in CA





No reported sales by largest distributors of equipment < 11 EER.

Results of Distributor Survey

- Current base case is SEER 13/EER 10
- Contacted distributors on EER sales data
 - Responsible for 100,000 units/yr
- All reported SEER 13 sales are EER 11+
- When a SEER13/EER11 unit is specified and EER verified, unearned credit is given
- CTZ 15 7% unearned compliance margin





EER 11 savings and impact on compliance margin by climate

	Single Family Dwelling Savings							
Climate Zone	TDV % Savings	TDV kBtu/sf	TDV kBtu/home	Savings kWh/yr	Peak kW			
1	0.00%	0	0	0	0.35			
2	1.00%	0.6	1533	36	0.34			
3	0.10%	0	57	2	0.36			
4	0.20%	0.1	233	4	0.26			
5	0.00%	0	16	0	0.25			
6	0.00%	0	0	0	0.27			
7	0.10%	0	44	1	0.27			
8	1.00%	0.4	950	18	0.26			
9	2.10%	1	2381	51	0.36			
10	3.20%	2	4752	121	0.39			
11	3.40%	2.9	7144	156	0.38			
12	2.20%	1.5	3613	75	0.34			
13	4.10%	3.5	8565	274	0.36			
14	3.90%	3.5	8584	227	0.41			
15	7.10%	7.6	18499	688	0.42			
16	0.40%	0.4	878	17	0.38			



Pacific Gas and Electric Company.

EER in ACM

Statewide first year energy savings

- Conservative assumes only 10% take HERS credit in all climates
 - Only calculated for res, more if include nonres
- Energy 1.6 GWh/yr (2% of total res savings)
- Demand 3.7 MW (12% of total res savings)
- 940 tons/yr CO₂ emissions
- Annual savings 10 times as much at the end of 10 years
- All from a minor change to the ACM





Cost-effectiveness

- This measure does not require a special air conditioner.
 - The minimally compliant air conditioner will still comply
- This measure does not require efficiency levels higher than the prescriptive levels
 - As long as prescriptive requirements are costeffective, so is this change





Proposed change – Res ACM

- The EER used for calculating the energy consumption of a SEER rated standard central air conditioner shall be the lesser of the EER rating of the air conditioner used in the proposed design or the default EER calculated in Equation R4-41 for the SEER value meeting the Appliance Efficiency Regulations minimum requirements.
- RACM Section 4.7.1 Cooling System Energy Equation R4-41
- Strike

Replace with

• <u>SEER < 12.7</u> <u>EER = 0.455 + SEER x 0.83</u> <u>SEER >= 12.7</u> <u>EER = 11.0</u>





Proposed Change Nonres ACM

Equation N2-2 EER67,95 = From Manufacturer Data [when available]

Strike

Replace with



